

EPOSIR[®] WD 705

PRODUCT
DATA SHEET
RE/WD 705/0605130/1

Description

Formulated epoxy-phenolic one-pack system in aqueous dispersion.

Applications

Eposir WD 705 is suitable for oven curing stoving paints and enamels for heavy duty protection.

Sales specification

Property	Value	Unit	Method
Solid content	39 – 41	%	SIR 10553
Viscosity at 20°C (Ford cup ø 4)	15 – 40	Sec	ASTM D 1200

Supply Form

- Drums 220 Kg
- Bulk
- Containers.

Storage stability

The product is stable for six months if stored in original containers, at temperature ranging from 10°C to 30°C. The material if exposed at temperature below 0°C can freeze. Freezing conditions or elevated temperatures will accelerate particle settling.

Safety

The product is not subjected to any labelling under the current regulations.
Further advice is given in the safety data sheet.

Eposir[®]: SIR INDUSTRIALE registered trade mark.

N.B.: The data given in this brochure do not constitute characteristic properties of the single product.

To our best knowledge, the information contained in this brochure is accurate and corresponds to the truth.

However, any recommendations or suggestions are provided without any guarantee, since the conditions in which the products are used are not under our control. Furthermore, nothing contained in this brochure shall be interpreted as a recommendation for using the product in violation of any patents relating to the material and their uses.