

SIRION[®] CE 2308

PRODUCT DATA
SHEET
REM/CE2308/020207/1

Description

Hydrogenated Bisphenol A based cycloaliphatic epoxy resin.

Applications

Modifier for epoxy systems. Good U.V. resistance. Suitable for outdoor applications, for high solid systems and oven-cured industrial maintenance and decorative paints. Suitable also as modifier for industrial acrylic finishes.

Sales specification

Property	Value	Unit	Method
Epoxy equivalent weight	230 – 260	g.	ISO 3001
Dynamic viscosity at 25°C	4000 – 8000	mPa.s.	ASTM D 0445
Gardner colour	2 max	Sc. Pt/Co	ASTM D 1209

Typical Properties

Property	Value	Unit	Method
Density at 25°C	1.14	g/cm ³	ASTM D 1475

Supply Form

- Drums 220 Kg

Storage stability

The product should be stored in the original containers, in dry ambient, protected against light and direct sun-rays, at temperature ranging from 15 to 30°C. In these conditions it is stable for one year.

Safety

The product is labelled as Irritant and we haven't noticed any toxic effects.
Further advice are given in the safety data sheet.

Sirion[®]: SIR INDUSTRIALE registered trade mark.

N.B.: The data given in this brochure do not constitute characteristic properties of the single product.

To our best knowledge, the information contained in this brochure is accurate and corresponds to the truth.

However, any recommendations or suggestions are provided without any guarantee, since the conditions in which the products are used are not under our control. Furthermore, nothing contained in this brochure shall be interpreted as a recommendation for using the product in violation of any patents relating to the material and their uses.