# SIRALES® PE 8425.T

PRODUCT DATA SHEET

RS/8425/021401/1

### **Description**

Carboxylated polyester resin, free from trimellitic anhydride, suitable for hybrid powder coatings. *Experimental resin. The specifications could be refined without any notice. In case of any question, please contact our sales department.* 

# **Applications**

Sirales<sup>®</sup> PE 8425.T is suggested in combination 70/30 p.b.w. with Eposir<sup>®</sup> 7178 PG, Eposir<sup>®</sup> 7175 PG and Eponac<sup>®</sup> 825, to manufacture powder coatings with high reactivity combined with good flow, good mechanical properties and good pverbaling resistance.

Powder coatings manufactured with Sirales® PE 8425.T are suitable for tribo gun applications.

**Curing cycles (real time)** 

15 min. at 170°C 20 min. at 160°C

**Sales specification** 

Property	Value	Unit	Method
Acid number	30 38	mg KOH/gr	SIR 10328
Viscosity at 200°C (ICI cone plate)	3500 5500	m.Pa.s.	SIR 10391
Colour (1)	3 max.	Sc. Gardner	ASTM D 1544

<sup>(1)</sup> Determined on 50% m/m solution on dimethylformamide.

# **Typical Properties**

Property	Value	Unit	Method
Glass transition temperature	54	$^{\circ}\mathrm{C}$	ASTM D 3418

#### **Supply Form**

Product is available as irregular flakes packed in 25 kg Polyethylene bags.

## **Storage stability**

The product should be stored in the original bags kept tightly closed, away from sunshine and heat sources. Under these conditions and at a normal temperature (20°C) the resin should have a stability of one year.

## **Safety**

The product is not flammable and no toxic effect has been determined.

Further information are provided in the relevant safety data sheet.

 $SIRALES^{\circledR}$  ,  $EPOSIR^{\circledR}$  and  $EPONAC^{\circledR}$  : SIR INDUSTRIALE registered trade mark.

N.B.: The data given in this brochure do not constitute characteristic properties of the single product. To our best knowledge, the information contained in this brochure is accurate and corresponds to the truth.

However, any recommendations or suggestions are provided without any guarantee, since the conditions in which the products are used are not under our control. Furthermore, nothing contained in this brochure shall be interpreted as a recommendation for using the product in violation of any patents relating to the material and their uses.